



TUALAJ 4500-D CRPA GNSS ANTI-JAM SYSTEM

GENERAL DESCRIPTION

TUALCOM CRPA Anti-Jam GNSS Systems support critical missions by providing jam free GNSS signals and resilient PNT.

With its 4-element CRPA antenna, state-of-art digital controller and novel beamforming techniques TUALAJ 4500-D eliminates interference to ensure uninterrupted operation of GNSS receivers in the presence of up to 3 jamming sources in 5 different frequency bands. The set of protected active bands is pre-selectable amongst available options.

TUALAJ 4500-D supports various messaging formats and integrates seamlessly with civil and military GNSS receivers deployed on land/sea platforms and fixed installations. TUALAJ 4500-D also offers embedded high performance GNSS receiver as an option and allows SBAS signals to be utilized for increased accuracy and reliability.

TUALAJ 4500-D is encapsulated in specifically designed housing to withstand the harshest environmental conditions and therefore is especially suitable for maritime platforms. In addition to CRPA, protection performance is further improved using adaptive notch filtering and pulse blanking.

BENEFITS

- Protection against 3 jammers in all constellations and frequency bands
- Easy to install
- Plug and play integration into new or legacy platforms
- Immediate availability for urgent operational needs
- Compatible with all types of external GPS receivers and vehicle navigation systems, including M Code
- Compact Size
- Superior suppression performance
- Embedded GNSS receiver option
- Compatibility with military standards
- Resilient PNT

APPLICATION AREAS

- Naval and Coast Guard Platforms
- Armored Land Vehicles
- Maritime EW Protection
- Critical Infrastructure EW Protection
- Military Communications

TUALAJ 4500-D

CRPA GNSS ANTI-JAM SYSTEM



Dimensions (cm)

Diameter: Ø25

Height: 13.8

Weight (g)

4500

Power Consumption

Maximum 30 W

Antenna Array

4 Array CRPA Antenna

Simultaneous Independent Nulling

3

Simultaneously Protected Active Bands

Option 1

GPS (L1, L2, L5, L6), L Band Correction

GALILEO (E1, E5a, E5b, E6)

BEIDOU (B1, B2a, B2b, B3), SBAS

Option 2

GPS (L1, L2, L5), GLONASS (G1, G2)

GALILEO (E1, E5a), L Band Correction

BEIDOU (B1, B2a), SBAS

Nominal Wideband Suppression

>50 dB

Connectors

2 x D38999

1 x TNC

Operating Voltage

12-28 Vdc

Operating Temperature

-40 °C to +85 °C

Embedded GNSS Receiver

(Optional)

GPS (L1, L2), GLONASS (G1, G2),

Galileo (E1, E5b), BeiDou (B1I), SBAS,

QZSS (L1), RTCM Support

Environmental Tests

MIL-STD-810G

EMI / EMC

MIL-STD-461F

Data Interfaces

Ethernet (Optional)

Serial RS-232

Serial RS-485

TUALCOM ELEKTRONİK A.Ş.

+90 (312) 485 22 85

info@tualcom.com.tr

www.tualcom.com

